





---

<b>Description:</b>	Sulphated natural oil.
<b>Aspect:</b>	Light brown fluid liquid.
<b>Concentration:</b>	61,0 – 65,0%
<b>pH (sol. 10%):</b>	7,0 – 9,0
<b>Charge:</b>	Anionic
<b>Light and heat fastness:</b>	Excellent
<b>Acid and salt stability:</b>	Good
<b>Application:</b>	Fatliquoring.
<b>Properties:</b>	<p><b>UP SOFT® SH4</b> is a fatliquor based on a very high quality of natural sulphated oils. Indicated to use in buffed or full grain articles, where the tight and fine grain is required, as well as the full touch and fat spew resistance is necessary.</p> <p><b>UP SOFT® SH4</b> has good penetration and is very indicated for all types of leather articles, after the neutralization, without interfere in the adhesion quality of the finishes.</p> <p>It has good light and heat fastness.</p>
<b>Use guideline:</b>	<p><b>UP SOFT® SH4</b> can be used alone or combined with other anionic fatliquors of the <b>UP SOFT®</b> portfolio. We suggest to blend the fatliquors perfectly before to prepare the emulsion in water at 60°C, in 1:3 proportion.</p> <ul style="list-style-type: none"><li> Boot Napa: 5,0 – 8,0% over the shaved wet blue weight;</li><li> Shoe upper: 7,0 a 10,0% over the shaved wet blue weight;</li><li> Heavy vegetal retanned: 6,0 – 9,0% over the shaved wet blue weight.</li></ul>
<b>Storage:</b>	We recommend keeping the product sealed in the original package, in a clean and controlled environment, avoiding extreme temperatures.
	
<b>Package:</b>	190 Kg metal drums.